

The **l3pdfmeta** module

PDF standards

L^AT_EX PDF management testphase bundle

The L^AT_EX Project*

Version 0.95q, released 2022-07-08

1 **l3pdfmeta** documentation

This module sets up some tools and commands needed for PDF standards in general. The goal is to collect the requirements and to provide code to check and fulfill them.

In future it will probably also contain code to setup XMP-metadata. Until then XMP-metadata can be added by one of two mutual incompatible packages: **hyperxmp** and **pdfx**. Both packages aren't yet compatible with the new PDF management, but for **hyperxmp** some patches are provided, so the basic functions work.

1.1 Verifying requirements of PDF standards

Standards like pdf/A set requirements on a PDF: Some things have to be in the PDF, e.g. the catalog has to contain a `/Lang` entry and a colorprofile and an `/OutputIntent`, some other things are forbidden or restricted, e.g. the action dictionary of an annotation should not contain Javascript.

The **l3pdfmeta** module collects a number of relevant requirements, tries to enforce the ones which can be enforced and offers some tools for package authors to test if an action is allowed in the standard or not.

This is work in progress and more tests will be added. But it should be noted that it will probably never be possible to prevent all forbidden actions or enforce all required ones or even to simply check all of them. The commands here don't replace a check with an external validator.

Verifying against a PDF-standard involves two different tasks:

- Check if you are allowed to ignore the requirement.
- Decide which action to take if the answer to the first question is NO.

The following conditionals address the first task. Because of the second task a return value **FALSE** means that the standard requires you to do some special action. **TRUE** means that you can ignore this requirement.¹

*E-mail: latex-team@latex-project.org

¹One could also make the logic the other way round—there are arguments for both—but I had to decide.

In most cases it only matters if a requirement is in the standard, for example `Catalog_no_OCProperties` means “don’t use `/OCProperties` in the catalog”. For a small number of requirements it is also needed to test a user value against a standard value. For example, `named_actions` restricts the allowed named actions in an annotation of subtype `/Named`, in this case it is needed to check not only if the requirement is in the standard but also if the user value is in the allowed list.

```
\pdfmeta_standard_verify_p:n * \pdfmeta_standard_verify:n{<requirement>}
\pdfmeta_standard_verify:nTF *
```

This checks if `<requirement>` is listed in the standard. `FALSE` as result means that the requirement is in the standard and that probably some special action is required—which one depends on the requirement, see the descriptions below. `TRUE` means that the requirement is not there and so no special action is needed. This check can be used for simple requirements where neither a user nor a standard value is of importance.

```
\pdfmeta_standard_verify:nnTF \pdfmeta_standard_verify:nn{<requirement>}{<value>}
```

This checks if `<requirement>` is listed in the standard, if yes it tries to find a predefined test handler for the requirement and passes `<value>` and the value recorded in the standard to it. The handler returns `FALSE` if some special action is needed (e.g. if `<value>` violates the rule) and `TRUE` if no special action is needed. If no handler exists this commands works like `\pdfmeta_standard_verify:n`.

In some cases one needs to query the value in the standard, e.g. to correct a wrong minimal PDF version you need to know which version is required by `min_pdf_version`. For this two commands to access the value are provided:

```
\pdfmeta_standard_item:n * \pdfmeta_standard_item:n{<requirement>}
```

This retrieves the value of `<requirement>` and leaves it in the input. If the requirement isn’t in the standard the result is empty, that means that requirements not in the standard and requirement without values can not be distinguished here.

```
\pdfmeta_standard_get:nn \pdfmeta_standard_get:nn{<requirement>} <tl var>
```

This retrieves the value of `<requirement>` and stores it in the `<token list variable>`. If the `<requirement>` is not found the special value `\q_no_value` is used. The `<token list variable>` is assigned locally.

The following describe the requirements which can be currently tested. Requirements with a value should use `\pdfmeta_standard_verify:nn` or `\pdfmeta_standard_verify:nnN` to test a local value against the standard. The rule numbers refer to <https://docs.verapdf.org/validation/pdfa-part1/>

1.1.1 Simple tests without handler

outputintent_A requires to embed a color profile and reference it in a `/Outputintent` and that all output intents reference the same colorprofile. The value stores the subtype. *This requirement is detected and fulfilled by l3pdfmeta if the provided interface in \DocumentMetadata is used, see below.*

annot_flags in annotations the `Print` flag should be true, `Hidden`, `Invisible`, `NoView` should be false. *This requirement is detected and set by `l3pdfmeta` for annotations created with the `l3pdfannot`. A new check is only needed if the flags are changed or if links are created by other means.*

no_encryption don't encrypt

no_external_content no `/F`, `/FFilter`, or `/FDecodeParms` in stream dictionaries

no_embed_content no `/EF` key in filespec, no `/Type/EmbeddedFiles`. *This will be checked in future by `l3pdfmeta` for the files it embeds.* The restriction is set for only PDF/A-1b. PDF/A-2b and PDF/A-3b lifted this restriction: PDF/A-2b allows to embed other PDF documents conforming to either PDF/A-1 or PDF/A-2, and PDF/A-3 allows any embedded files. I don't see a way to test the PDF/A-2b requirement so currently it will simply allow everything. Perhaps a test for at least the PDF-format will be added in future.

Catalog_no_OCProperties don't add `/OCProperties` to the catalog *`l3pdfmeta` removes this entry at the end of the document*

annot_widget_no_AA (rule 6.6.2-1) no AA dictionary in widget annotation, this will e.g. be checked by the new hyperref driver.

annot_widget_no_A_AA (rule 6.9-2) no A and AA dictionary in widget.

form_no_AA (6.9-3) no `/AA` dictionary in form field

unicode that is set in the U-standards, A-2u and A-3u and means that every text should be in unicode. This is not something that can be enforced or tested from TeX, but in a current LaTeX normally `ToUnicode` are set for all fonts.

tagged that is set in A-2a and A-3a and means that the pdf must be tagged. This is currently neither tested not enforced somewhere.

Trailer_no_Info The `Info` dictionary has been deprecated since quite some time. Metadata should be set with XMP-data instead. In PDF A-4 now the `Info` dictionary shall not be present in the trailer dictionary at all (unless there exists a `PieceInfo` entry in the Catalog). And if it is present it should only contain the `/ModDate` entry. The engines do not offer currently an option to suppress the dictionary completely, one can only give the entries the value null (it only works for all entries with `lualatex` and `pdflatex`). The next `pdflatex` will offer `\pdfomitinfodict`. Until then `l3pdfmeta` does nothing with this requirement.

1.1.2 Tests with values and special handlers

min_pdf_version stores the minimal PDF version needed for a standard. It should be checked against the current PDF version (`\pdf_version:`). A failure means that the version should be changed. Currently there is only one hard requirement which leads to a failure in a validator like `verapdf`: The A-4 standard should use PDF 2.0. As PDF A-1 is based on PDF 1.4 and PDF A-2 and A-3 are based on PDF 1.7 `l3pdfmeta` also sets these versions also as requirements. These requirements are checked by `l3pdfmeta` when the version is set with `\DocumentMetadata` and a warning is issued (but the version is not changed). More checks are only needed if the version is changed later.

max_pdf_version stores the maximal PDF version. It should be checked against the current PDF version (`\pdf_version:`). A failure means that the version should be changed. The check is currently relevant only for the A-1 to A-3 standards: PDF 2.0 leads to a failure in a validator like verapdf so the maximal version should be PDF 1.7. This requirement is checked by `l3pdfmeta` when the version is set with `\DocumentMetadata` and a warning is issued (but the version is not changed). More checks are only needed if the version is changed later.

named_actions this requirement restricts the list of allowed named actions to `NextPage`, `PrevPage`, `FirstPage`, `LastPage`. The check should supply the named action without slash (e.g. `View` (failure) or `NextPage` (pass)).

annot_action_A (rule 6.6.1-1) this requirement restricts the allowed subtypes of the `/A` dictionary of an action. The check should supply the user subtype without slash e.g. as `GoTo` (pass) or `Movie` (failure).

1.2 Colorprofiles and OutputIntent

The pdf/A standards require that a color profile is embedded and referenced in the catalog in the `/OutputIntent` array.

The problem is that the pdf/A standards also require, that if the PDF has more than one entry in the `/OutputIntent` array (which is allowed), their `/DestOutputProfile` should all reference the same color profile².

Enforcing this fully is impossible if entries are added manually by users or packages with `\pdfmanagement_add:nnn {Catalog}{OutputIntents}{<object reference>}` as it is difficult to inspect and remove entries from the `/OutputIntent` array.

So we provide a dedicated interface to avoid the need of manual user settings and allow the code to handle the requirements of the standard. The interface doesn't handle yet all finer points for PDF/X standards, e.g. named profiles, it is meant as a starting point to get at least PDF/A validation here.

The interface looks like this

```
\DocumentMetadata
{
  %other options for example pdfstandard
  colorprofiles=
  {
    A = sRGB.icc, %or a or longer GTS_PDFA1 = sRGB.icc
    X = FOGRA39L_coated.icc, % or x or longer GTS_PDFX
    ISO_PDFE1 = whatever.icc
  }
}
```

`sRGB.icc` and `FOGRA39L_coated.icc` (from the `colorprofiles` package are predefined and will work directly³. `whatever.icc` will need special setup in the document preamble to declare the values for the `OutputIntent` dictionary, but the interface hasn't be added yet. This will be decided later.

²see rule 6.2.2-2 at <https://docs.verapdf.org/validation/pdfa-part1/>

³The `dvips` route will require that `ps2pdf` is called with `-dNOSAFER`, and that the color profiles are in the current folder as `ps2pdf` doesn't use `kpathsea` to find them.

If an A-standard is detected or set which requires that all `/DestOutputProfile` reference the same color profile, the setting is changed to the equivalent of

```
\DocumentMetadata
{
  %other options
  pdfstandard=A-2b,
  colorprofiles=
  {
    A = sRGB.icc, %or longer GTS_PDFA1 = sRGB.icc
    X = sRGB.icc,
    ISO_PDFE1 = sRGB.icc
  }
}
```

The pdf/A standards will use `A=sRGB.icc` by default, so this doesn't need to be declared explicitly.

1.3 Regression tests

When doing regression tests one has to set various metadata to fix values.

```
\pdfmeta_set_regression_data: \pdfmeta_set_regression_data:
```

This sets various metadata to values needed by the L^AT_EX regression tests. It also sets the seed for random functions.

2 l3pdfmeta implementation

```
1 <@@=pdfmeta>
2 <*header>
3 \ProvidesExplPackage{l3pdfmeta}{2022-07-08}{0.95q}
4 {PDF-Standards---LaTeX PDF management testphase bundle}
5 </header>
```

Message for unknown standards

```
6 <*package>
7 \msg_new:nnn {pdf }{unknown-standard}{The~standard~'#1'~is~unknown~and~has~been~ignored}
```

Message for not fitting pdf version

```
8 \msg_new:nnn {pdf }{wrong-pdfversion}
9 {PDF-version-#1-is-too-#2-for-standard-'#3'.}
```

```
\l__pdfmeta_tmpa_tl
\l__pdfmeta_tmppb_tl
\l__pdfmeta_tmppa_str
```

```
10 \tl_new:N\l__pdfmeta_tmpa_tl
11 \tl_new:N\l__pdfmeta_tmppb_tl
12 \str_new:N \l__pdfmeta_tmppa_str
```

(End definition for `\l__pdfmeta_tmpa_tl`, `\l__pdfmeta_tmppb_tl`, and `\l__pdfmeta_tmppa_str`.)

2.1 Standards (work in progress)

2.1.1 Tools and tests

This internal property will contain for now the settings for the document.

`\g__pdfmeta_standard_prop`

```
13 \prop_new:N \g__pdfmeta_standard_prop
```

(End definition for \g__pdfmeta_standard_prop.)

2.1.2 Functions to check a requirement

At first two commands to get the standard value if needed:

`\pdfmeta_standard_item:n`

```
14 \cs_new:Npn \pdfmeta_standard_item:n #1
15 {
16   \prop_item:Nn \g__pdfmeta_standard_prop {#1}
17 }
```

(End definition for \pdfmeta_standard_item:n. This function is documented on page 2.)

`\pdfmeta_standard_get:nN`

```
18 \cs_new_protected:Npn \pdfmeta_standard_get:nN #1 #2
19 {
20   \prop_get:NnN \g__pdfmeta_standard_prop {#1} #2
21 }
```

(End definition for \pdfmeta_standard_get:nN. This function is documented on page 2.)

Now two functions to check the requirement. A simple and one value/handler based.

`\pdfmeta_standard_verify_p:n`
`\pdfmeta_standard_verify:nTF`

This is a simple test is the requirement is in the prop.

```
22 \prg_new_conditional:Npnn \pdfmeta_standard_verify:n #1 {T,F,TF}
23 {
24   \prop_if_in:NnTF \g__pdfmeta_standard_prop {#1}
25   {
26     \prg_return_false:
27   }
28   {
29     \prg_return_true:
30   }
31 }
```

(End definition for \pdfmeta_standard_verify:nTF. This function is documented on page 2.)

`\pdfmeta_standard_verify:nnTF`

This allows to test against a user value. It calls a test handler if this exists and passes the user and the standard value to it. The test handler should return true or false.

```
32 \prg_new_protected_conditional:Npnn \pdfmeta_standard_verify:nn #1 #2 {T,F,TF}
33 {
34   \prop_if_in:NnTF \g__pdfmeta_standard_prop {#1}
35   {
36     \cs_if_exist:cTF {__pdfmeta_standard_verify_handler_#1:nn}
37     {
38       \exp_args:Nnnx
39       \use:c
```

```

40         {__pdfmeta_standard_verify_handler_#1:nn}
41         { #2 }
42         { \prop_item:Nn \g__pdfmeta_standard_prop {#1} }
43     }
44     {
45         \prg_return_false:
46     }
47 }
48 {
49     \prg_return_true:
50 }
51 }

```

(End definition for \pdfmeta_standard_verify:nnTF. This function is documented on page 2.)

Now we setup a number of handlers.

The first actually ignores the user values and tests against the current pdf version. If this is smaller than the minimum we report a failure. #1 is the user value, #2 the reference value from the standard.

_standard_verify_handler_min_pdf_version:nn

```

52 %
53 \cs_new_protected:Npn \__pdfmeta_standard_verify_handler_min_pdf_version:nn #1 #2
54 {
55     \pdf_version_compare:NnTF <
56         { #2 }
57         {\prg_return_false:}
58         {\prg_return_true:}
59 }

```

(End definition for __pdfmeta_standard_verify_handler_min_pdf_version:nn.)

The next is the counter part and checks that the version is not to high

_standard_verify_handler_max_pdf_version:nn

```

60 %
61 \cs_new_protected:Npn \__pdfmeta_standard_verify_handler_max_pdf_version:nn #1 #2
62 {
63     \pdf_version_compare:NnTF >
64         { #2 }
65         {\prg_return_false:}
66         {\prg_return_true:}
67 }

```

(End definition for __pdfmeta_standard_verify_handler_max_pdf_version:nn.)

The next checks if the user value is in the list and returns a failure if not.

ta_standard_verify_handler_named_actions:nn

```

68
69 \cs_new_protected:Npn \__pdfmeta_standard_verify_handler_named_actions:nn #1 #2
70 {
71     \tl_if_in:nnTF { #2 }{ #1 }
72     {\prg_return_true:}
73     {\prg_return_false:}
74 }

```

(End definition for __pdfmeta_standard_verify_handler_named_actions:nn.)

The next checks if the user value is in the list and returns a failure if not.

a_standard_verify_handler_annot_action_A:nn

```
75 \cs_new_protected:Npn \__pdfmeta_standard_verify_handler_annot_action_A:nn #1 #2
76 {
77   \tl_if_in:nnTF { #2 }{ #1 }
78     {\prg_return_true:}
79     {\prg_return_false:}
80 }
```

(End definition for __pdfmeta_standard_verify_handler_annot_action_A:nn.)

This check is probably not needed, but for completeness

dard_verify_handler_outputintent_subtype:nn

```
81 \cs_new_protected:Npn \__pdfmeta_standard_verify_handler_outputintent_subtype:nn #1 #2
82 {
83   \tl_if_eq:nnTF { #2 }{ #1 }
84     {\prg_return_true:}
85     {\prg_return_false:}
86 }
```

(End definition for __pdfmeta_standard_verify_handler_outputintent_subtype:nn.)

2.1.3 Enforcing requirements

A number of requirements can sensibly be enforced by us.

Annot flags pdf/A require a number of settings here, we store them in a command which can be added to the property of the standard:

```
87 \cs_new_protected:Npn \__pdfmeta_verify_pdfa_annot_flags:
88 {
89   \bitset_set_true:Nn \l_pdfannot_F_bitset {Print}
90   \bitset_set_false:Nn \l_pdfannot_F_bitset {Hidden}
91   \bitset_set_false:Nn \l_pdfannot_F_bitset {Invisible}
92   \bitset_set_false:Nn \l_pdfannot_F_bitset {NoView}
93   \pdfannot_dict_put:nnn {link/URI}{F}{ \bitset_to_arabic:N \l_pdfannot_F_bitset }
94   \pdfannot_dict_put:nnn {link/GoTo}{F}{ \bitset_to_arabic:N \l_pdfannot_F_bitset }
95   \pdfannot_dict_put:nnn {link/GoToR}{F}{ \bitset_to_arabic:N \l_pdfannot_F_bitset }
96   \pdfannot_dict_put:nnn {link/Launch}{F}{ \bitset_to_arabic:N \l_pdfannot_F_bitset }
97   \pdfannot_dict_put:nnn {link/Named}{F}{ \bitset_to_arabic:N \l_pdfannot_F_bitset }
98 }
```

At begin document this should be checked:

```
99 \hook_gput_code:nnn {begindocument} {pdf}
100 {
101   \pdfmeta_standard_verify:nF { annot_flags }
102   { \__pdfmeta_verify_pdfa_annot_flags: }
103   \pdfmeta_standard_verify:nnF { min_pdf_version }
104   { \pdf_version: }
105   { \msg_warning:nnxxx {pdf}{wrong-pdfversion}
106     {\pdf_version:}{low}
107   }
108   \pdfmeta_standard_item:n{type}
109   -
110   \pdfmeta_standard_item:n{level}
111 }
```



```

112     }
113     \pdfmeta_standard_verify:nnF { max_pdf_version }
114     { \pdf_version: }
115     { \msg_warning:nnxxx {pdf}{wrong-pdfversion}
116       {\pdf_version:}{high}
117       {
118         \pdfmeta_standard_item:n{type}
119         -
120         \pdfmeta_standard_item:n{level}
121       }
122     }
123   }

```

2.1.4 pdf/A

We use global properties so that follow up standards can be copied and then adjusted. Some note about requirements for more standard can be found in `info/pdfstandard.tex`.

```

\g__pdfmeta_standard_pdf/A-1B_prop
\g__pdfmeta_standard_pdf/A-2A_prop
\g__pdfmeta_standard_pdf/A-2B_prop
\g__pdfmeta_standard_pdf/A-2U_prop
\g__pdfmeta_standard_pdf/A-3A_prop
\g__pdfmeta_standard_pdf/A-3B_prop
\g__pdfmeta_standard_pdf/A-3U_prop
\g__pdfmeta_standard_pdf/A-4_prop
124 \prop_new:c { g__pdfmeta_standard_pdf/A-1B_prop }
125 \prop_gset_from_keyval:cn { g__pdfmeta_standard_pdf/A-1B_prop }
126 {
127     ,name           = pdf/A-1B
128     ,type           = A
129     ,level          = 1
130     ,conformance    = B
131     ,year           = 2005
132     ,min_pdf_version = 1.4           %minimum
133     ,max_pdf_version = 1.4           %minimum
134     ,no_encryption  =
135     ,no_external_content = % no F, FFilter, or FDecodeParms in stream dicts
136     ,no_embed_content = % no EF key in filespec, no /Type/EmbeddedFiles
137     ,max_string_size = 65535
138     ,max_array_size  = 8191
139     ,max_dict_size   = 4095
140     ,max_obj_num     = 8388607
141     ,max_nest_qQ      = 28
142     ,named_actions   = {NextPage, PrevPage, FirstPage, LastPage}
143     ,annot_flags     =
144     %booleans. Only the existence of the key matter.
145     %If the entry is added it means a requirements is there
146     %(in most cases "don't use ...")
147     %
148     %=====
149     % Rule 6.1.13-1 CosDocument, isOptionalContentPresent == false
150     ,Catalog_no_OCProperties =
151     %=====
152     % Rule 6.6.1-1: PDAction, S == "GoTo" || S == "GoToR" || S == "Thread"
153     % || S == "URI" || S == "Named" || S == "SubmitForm"
154     % means: no /S/Launch, /S/Sound, /S/Movie, /S/ResetForm, /S/ImportData,
155     % /S/JavaScript, /S/Hide
156     ,annot_action_A   = {GoTo,GoToR,Thread,URI,Named,SubmitForm}
157     %=====
158     % Rule 6.6.2-1: PDAnnot, Subtype != "Widget" || AA_size == 0

```

```

159 % means: no AA dictionary
160 ,annot_widget_no_AA =
161 %=====
162 % Rule 6.9-2: PDAnnot, Subtype != "Widget" || (A_size == 0 && AA_size == 0)
163 % (looks like a tightening of the previous rule)
164 ,annot_widget_no_A_AA =
165 %=====
166 % Rule 6.9-1 PDAcroForm, NeedAppearances == null || NeedAppearances == false
167 ,form_no_NeedAppearances =
168 %=====
169 %Rule 6.9-3 PDFFormField, AA_size == 0
170 ,form_no_AA =
171 %=====
172 % to be continued https://docs.verapdf.org/validation/pdfa-part1/
173 % - Outputintent/colorprofiles requirements
174 % an outputintent should be loaded and is unique.
175 ,outputintent_A = {GTS_PDFA1}
176 % - no Alternates key in image dictionaries
177 % - no OPI, Ref, Subtype2 with PS key in xobjects
178 % - Interpolate = false in images
179 % - no TR, TR2 in ExtGstate
180 }
181
182 %A-2b =====
183 \prop_new:c { g__pdfmeta_standard_pdf/A-2B_prop }
184 \prop_gset_eq:cc
185 { g__pdfmeta_standard_pdf/A-2B_prop }
186 { g__pdfmeta_standard_pdf/A-1B_prop }
187 \prop_gput:cnn
188 { g__pdfmeta_standard_pdf/A-2B_prop }{name}{pdf/A-2B}
189 \prop_gput:cnn
190 { g__pdfmeta_standard_pdf/A-2B_prop }{year}{2011}
191 \prop_gput:cnn
192 { g__pdfmeta_standard_pdf/A-2B_prop }{level}{2}
193 % embedding files is allowed (with restrictions)
194 \prop_gremove:cn
195 { g__pdfmeta_standard_pdf/A-2B_prop }
196 { embed_content}
197 \prop_gput:cnn
198 { g__pdfmeta_standard_pdf/A-2B_prop }{max_pdf_version}{1.7}
199 %A-2u =====
200 \prop_new:c { g__pdfmeta_standard_pdf/A-2U_prop }
201 \prop_gset_eq:cc
202 { g__pdfmeta_standard_pdf/A-2U_prop }
203 { g__pdfmeta_standard_pdf/A-2B_prop }
204 \prop_gput:cnn
205 { g__pdfmeta_standard_pdf/A-2U_prop }{name}{pdf/A-2U}
206 \prop_gput:cnn
207 { g__pdfmeta_standard_pdf/A-2U_prop }{conformance}{U}
208 \prop_gput:cnn
209 { g__pdfmeta_standard_pdf/A-2U_prop }{unicode}{ }
210
211 %A-2a =====
212 \prop_new:c { g__pdfmeta_standard_pdf/A-2A_prop }

```

```

213 \prop_gset_eq:cc
214 { g__pdfmeta_standard_pdf/A-2A_prop }
215 { g__pdfmeta_standard_pdf/A-2B_prop }
216 \prop_gput:cnn
217 { g__pdfmeta_standard_pdf/A-2A_prop }{name}{pdf/A-2A}
218 \prop_gput:cnn
219 { g__pdfmeta_standard_pdf/A-2A_prop }{conformance}{A}
220 \prop_gput:cnn
221 { g__pdfmeta_standard_pdf/A-2A_prop }{tagged}{}
222
223
224 %A-3b =====
225 \prop_new:c { g__pdfmeta_standard_pdf/A-3B_prop }
226 \prop_gset_eq:cc
227 { g__pdfmeta_standard_pdf/A-3B_prop }
228 { g__pdfmeta_standard_pdf/A-2B_prop }
229 \prop_gput:cnn
230 { g__pdfmeta_standard_pdf/A-3B_prop }{name}{pdf/A-3B}
231 \prop_gput:cnn
232 { g__pdfmeta_standard_pdf/A-3B_prop }{year}{2012}
233 \prop_gput:cnn
234 { g__pdfmeta_standard_pdf/A-3B_prop }{level}{3}
235 % embedding files is allowed (with restrictions)
236 \prop_gremove:cn
237 { g__pdfmeta_standard_pdf/A-3B_prop }
238 { embed_content}
239 %A-3u =====
240 \prop_new:c { g__pdfmeta_standard_pdf/A-3U_prop }
241 \prop_gset_eq:cc
242 { g__pdfmeta_standard_pdf/A-3U_prop }
243 { g__pdfmeta_standard_pdf/A-3B_prop }
244 \prop_gput:cnn
245 { g__pdfmeta_standard_pdf/A-3U_prop }{name}{pdf/A-3U}
246 \prop_gput:cnn
247 { g__pdfmeta_standard_pdf/A-3U_prop }{conformance}{U}
248 \prop_gput:cnn
249 { g__pdfmeta_standard_pdf/A-3U_prop }{unicode}{}
250
251 %A-3a =====
252 \prop_new:c { g__pdfmeta_standard_pdf/A-3A_prop }
253 \prop_gset_eq:cc
254 { g__pdfmeta_standard_pdf/A-3A_prop }
255 { g__pdfmeta_standard_pdf/A-3B_prop }
256 \prop_gput:cnn
257 { g__pdfmeta_standard_pdf/A-3A_prop }{name}{pdf/A-3A}
258 \prop_gput:cnn
259 { g__pdfmeta_standard_pdf/A-3A_prop }{conformance}{A}
260 \prop_gput:cnn
261 { g__pdfmeta_standard_pdf/A-3A_prop }{tagged}{}
262
263 %A-4 =====
264 \prop_new:c { g__pdfmeta_standard_pdf/A-4_prop }
265 \prop_gset_eq:cc
266 { g__pdfmeta_standard_pdf/A-4_prop }

```

```

267 { g__pdfmeta_standard_pdf/A-3U_prop }
268 \prop_gput:cnn
269 { g__pdfmeta_standard_pdf/A-4_prop }{name}{pdf/A-4}
270 \prop_gput:cnn
271 { g__pdfmeta_standard_pdf/A-4_prop }{level}{4}
272 \prop_gput:cnn
273 { g__pdfmeta_standard_pdf/A-4_prop }{min_pdf_version}{2.0}
274 \prop_gput:cnn
275 { g__pdfmeta_standard_pdf/A-4_prop }{year}{2020}
276 \prop_gput:cnn
277 { g__pdfmeta_standard_pdf/A-4_prop }{Trailer_no_Info}{ }
278 \prop_gremove:cn
279 { g__pdfmeta_standard_pdf/A-4_prop }{conformance}
280 \prop_gremove:cn
281 { g__pdfmeta_standard_pdf/A-4_prop }{max_pdf_version}
(End definition for \g__pdfmeta_standard_pdf/A-1B_prop and others.)

```

2.1.5 Colorprofiles and Outputintents

The following provides a minimum of interface to add a color profile and an outputintent need for PDF/A for now. There will be need to extend it later, so we try for enough generality.

Adding a profile and an intent is technically easy:

1. Embed the profile as stream with

```
\pdf_object_unnamed_write:nn{fstream} {{/N~4}{XXX.icc}}
```

2. Write a /OutputIntent dictionary for this

```

\pdf_object_unnamed_write:nx {dict}
{
  /Type /OutputIntent
  /S /GTS_PDFA1 % or GTS_PDFX or ISO_PDFE1 or ...
  /DestOutputProfile \pdf_object_ref_last: % ref the color profile
  /OutputConditionIdentifier ...
  ... %more info
}

```

3. Reference the dictionary in the catalog:

```
\pdfmanagement_add:nxx {Catalog}{OutputIntents}{\pdf_object_ref_last:}
```

But we need to do a bit more work, to get the interface right. The object for the profile should be named, to allow l3color to reuse it if needed. And we need container to store the profiles, to handle the standard requirements.

`\g__pdfmeta_outputintents_prop` This variable will hold the profiles for the subtypes. We assume that every subtype has only only color profile.

```
282 \prop_new:N \g__pdfmeta_outputintents_prop
```

(End definition for \g__pdfmeta_outputintents_prop.)

Some keys to fill the property.

```
283 \keys_define:nn { document / metadata }
284 {
285   colorprofiles .code:n =
286   {
287     \keys_set:nn { document / metadata / colorprofiles }{#1}
288   }
289 }
290 \keys_define:nn { document / metadata / colorprofiles }
291 {
292   ,A .code:n =
293   {
294     \tl_if_blank:nF {#1}
295     {
296       \prop_gput:Nnn \g__pdfmeta_outputintents_prop
297       { GTS_PDFA1 } {#1}
298     }
299   }
300   ,a .code:n =
301   {
302     \tl_if_blank:nF {#1}
303     {
304       \prop_gput:Nnn \g__pdfmeta_outputintents_prop
305       { GTS_PDFA1 } {#1}
306     }
307   }
308   ,X .code:n =
309   {
310     \tl_if_blank:nF {#1}
311     {
312       \prop_gput:Nnn \g__pdfmeta_outputintents_prop
313       { GTS_PDFX } {#1}
314     }
315   }
316   ,x .code:n =
317   {
318     \tl_if_blank:nF {#1}
319     {
320       \prop_gput:Nnn \g__pdfmeta_outputintents_prop
321       { GTS_PDFX } {#1}
322     }
323   }
324   ,unknown .code:n =
325   {
326     \tl_if_blank:nF {#1}
327     {
328       \exp_args:NNo
329       \prop_gput:Nnn \g__pdfmeta_outputintents_prop
330       { \l_keys_key_str } {#1}
331     }
332   }
333 }
```

At first we setup our two default profiles. This is internal as the public interface is still undecided.

```

334 \pdfdict_new:n {l_pdfmeta/outputintent}
335 \pdfdict_put:nnn {l_pdfmeta/outputintent}
336 {Type}{/OutputIntent}
337 \prop_const_from_keyval:cn { c__pdfmeta_colorprofile_sRGB.icc}
338 {
339   ,OutputConditionIdentifier=IEC~sRGB
340   ,Info=IEC~61966-2.1~Default~RGB~colour~space~~~sRGB
341   ,RegistryName=http://www.iec.ch
342   ,N = 3
343 }
344 \prop_const_from_keyval:cn { c__pdfmeta_colorprofile_FOGRA39L_coated.icc}
345 {
346   ,OutputConditionIdentifier=FOGRA39L~Coated
347   ,Info={Offset~printing,~according~to~ISO~12647-2:2004/Amd~1,~OFDCOM,~ %
348     paper~type~1~or~2~==~coated~art,~115~g/m2,~tone~value~increase~
349     curves~A~(CMY)~and~B~(K)}
350   ,RegistryName=http://www.fogra.org
351   ,N = 4
352 }

```

__pdfmeta_embed_colorprofile:n
 __pdfmeta_write_outputintent:nn

The commands embed the profile, and write the dictionary and add it to the catalog. The first command should perhaps be moved to l3color as it needs such profiles too. We used named objects so that we can check if the profile is already there. This is not full proof if pathes are used.

```

353 \cs_new_protected:Npn \__pdfmeta_embed_colorprofile:n #1%#1 file name
354 {
355   \pdf_object_if_exist:nF { __color_icc_ #1 }
356   {
357     \pdf_object_new:nn { __color_icc_ #1 }{fstream}
358     \pdf_object_write:nx { __color_icc_ #1 }
359     {
360       {/N\c_space_tl
361         \prop_item:cn{c__pdfmeta_colorprofile_#1}{N}
362       }
363       {#1}
364     }
365   }
366 }
367
368 \cs_new_protected:Npn \__pdfmeta_write_outputintent:nn #1 #2 %#1 file name, #2 subtype
369 {
370   \group_begin:
371   \pdfdict_put:nnx {l_pdfmeta/outputintent}{S}{/\str_convert_pdfname:n{#2}}
372   \pdfdict_put:nnx {l_pdfmeta/outputintent}
373   {DestOutputProfile}
374   {\pdf_object_ref:n{ __color_icc_ #1 }}
375   \clist_map_inline:nn { OutputConditionIdentifier, Info, RegistryName }
376   {
377     \prop_get:cnNT
378     { c__pdfmeta_colorprofile_#1}
379     { #1 }

```

```

380     \l__pdfmeta_tmpa_tl
381     {
382         \pdf_string_from_unicode:nVN {utf8/string}\l__pdfmeta_tmpa_tl\l__pdfmeta_tmpa_str
383         \pdfdict_put:nnx
384         {l__pdfmeta/outputintent}{##1}{\l__pdfmeta_tmpa_str}
385     }
386 }
387 \pdf_object_unnamed_write:nx {dict}{\pdfdict_use:n {l__pdfmeta/outputintent} }
388 \pdfmanagement_add:nnx {Catalog}{OutputIntents}{\pdf_object_ref_last:}
389 \group_end:
390 }

```

(End definition for __pdfmeta_embed_colorprofile:n and __pdfmeta_write_outputintent:nn.)

Now the verifying code. If no requirement is set we simply loop over the property

```

391
392 \AddToHook{begindocument/end}
393 {
394     \pdfmeta_standard_verify:nTF {outputintent_A}
395     {
396         \prop_map_inline:Nn \g__pdfmeta_outputintents_prop
397         {
398             \__pdfmeta_embed_colorprofile:n
399             {#2}
400             \__pdfmeta_write_outputintent:nn
401             {#2}
402             {#1}
403         }
404     }

```

If an output intent is required for pdf/A we need to ensure, that the key of default subtype has a value, as default we take sRGB.icc. Then we loop but take always the same profile.

```

405     {
406         \exp_args:NNx
407         \prop_if_in:NnF
408         \g__pdfmeta_outputintents_prop
409         { \pdfmeta_standard_item:n { outputintent_A } }
410         {
411             \exp_args:NNx
412             \prop_gput:Nnn
413             \g__pdfmeta_outputintents_prop
414             { \pdfmeta_standard_item:n { outputintent_A } }
415             { sRGB.icc }
416         }
417         \exp_args:NNx
418         \prop_get:NnN
419         \g__pdfmeta_outputintents_prop
420         { \pdfmeta_standard_item:n { outputintent_A } }
421         \l__pdfmeta_tmpb_tl
422         \exp_args:NV \__pdfmeta_embed_colorprofile:n \l__pdfmeta_tmpb_tl
423         \prop_map_inline:Nn \g__pdfmeta_outputintents_prop
424         {
425             \exp_args:NV
426             \__pdfmeta_write_outputintent:nn

```

```

427         \l__pdfmeta_tmpb_tl
428         { #1 }
429     }
430 }
431 }

```

2.2 Regression test

This is simply a copy of the backend function.

```

432 \cs_new_protected:Npn \pdfmeta_set_regression_data:
433 { \__pdf_backend_set_regression_data: }
434 </package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A		H	
\AddToHook 392	hook commands:	
		\hook_gput_code:nnn 99
B		K	
bitset commands:		keys commands:	
\bitset_set_false:Nn 90, 91, 92	\keys_define:nn 283, 290
\bitset_set_true:Nn 89	\l_keys_key_str 330
\bitset_to_arabic:N	93, 94, 95, 96, 97	\keys_set:nn 287
C		M	
clist commands:		msg commands:	
\clist_map_inline:nn 375	\msg_new:nnn 7, 8
cs commands:		\msg_warning:nnnnn 105, 115
\cs_if_exist:NTF 36		
\cs_new:Npn 14		
\cs_new_protected:Npn 18,		
	53, 61, 69, 75, 81, 87, 353, 368, 432		
D		P	
\DocumentMetadata 2–4	pdf commands:	
E		\pdf_object_if_exist:nTF 355
exp commands:		\pdf_object_new:nn 357
\exp_args:Nnnx 38	\pdf_object_ref:n 374
\exp_args:NNo 328	\pdf_object_ref_last: 388
\exp_args:NNx 406, 411, 417	\pdf_object_unnamed_write:nn	.. 387
\exp_args:NV 422, 425	\pdf_object_write:nn 358
G		\pdf_string_from_unicode:nnN	.. 382
group commands:		\pdf_version:	.. 3, 4, 104, 106, 114, 116
\group_begin: 370	\pdf_version_compare:NnTF	... 55, 63
\group_end: 389	pdf internal commands:	
		__pdf_backend_set_regression_	
		data: 433
		pdfannot commands:	
		\pdfannot_dict_put:nnn
		 93, 94, 95, 96, 97

\l_pdfannot_F_bitset	__pdfmeta_standard_verify_-
.... 89, 90, 91, 92, 93, 94, 95, 96, 97	handler_outputintent_subtype:nn
pdfdict commands: 81, 81
\pdfdict_new:n	\l__pdfmeta_tmpa_str ... 10, 382, 384
334	\l__pdfmeta_tmpa_tl ... 10, 380, 382
\pdfdict_put:nnn ... 335, 371, 372, 383	\l__pdfmeta_tmpb_tl . 10, 421, 422, 427
\pdfdict_use:n	__pdfmeta_verify_pdfa_annot_-
387	flags:
pdfmanagement commands:	87, 102
\pdfmanagement_add:nnn	__pdfmeta_write_outputintent:nn
388 353, 368, 400, 426
pdfmeta commands:	\pdfomitinfodict
\pdfmeta_set_regression_data: 5, 432	3
\pdfmeta_standard_get:nN ... 2, 18, 18	prg commands:
\pdfmeta_standard_item:n	\prg_new_conditional:Npnn
2,	22
14, 14, 108, 110, 118, 120, 409, 414, 420	\prg_new_protected_conditional:Npnn
\pdfmeta_standard_verify:n ... 2, 22 32
\pdfmeta_standard_verify:nn ... 2, 32	\prg_return_false:
\pdfmeta_standard_verify:nnN ... 2 26, 45, 57, 65, 73, 79, 85
\pdfmeta_standard_verify:nnTF ...	\prg_return_true:
..... 2, 32, 103, 113 29, 49, 58, 66, 72, 78, 84
\pdfmeta_standard_verify:nTF ...	prop commands:
..... 2, 22, 101, 394	\prop_const_from_keyval:Nn . 337, 344
\pdfmeta_standard_verify_p:n . 2, 22	\prop_get:NnN
pdfmeta internal commands:	20, 418
__pdfmeta_embed_colorprofile:n .	\prop_get:NnNTF
..... 353, 353, 398, 422	377
\g__pdfmeta_outputintents_prop ..	\prop_gput:Nnn
..... 282, 296, 304,	187,
312, 320, 329, 396, 408, 413, 419, 423	189, 191, 197, 204, 206, 208, 216,
\g__pdfmeta_standard_pdf/A-1B_-	218, 220, 229, 231, 233, 244, 246,
prop	248, 256, 258, 260, 268, 270, 272,
124	274, 276, 296, 304, 312, 320, 329, 412
\g__pdfmeta_standard_pdf/A-2A_-	\prop_gremove:Nn ... 194, 236, 278, 280
prop	\prop_gset_eq:NN
124 184, 201, 213, 226, 241, 253, 265
\g__pdfmeta_standard_pdf/A-2B_-	\prop_gset_from_keyval:Nn
prop	125
124	\prop_if_in:NnTF
\g__pdfmeta_standard_pdf/A-2U_-	24, 34, 407
prop	\prop_item:Nn
124	16, 42, 361
\g__pdfmeta_standard_pdf/A-3A_-	\prop_map_inline:Nn
prop	396, 423
124	\prop_new:N
\g__pdfmeta_standard_pdf/A-3B_-	13, 124,
prop	183, 200, 212, 225, 240, 252, 264, 282
124	\ProvidesExplPackage
\g__pdfmeta_standard_pdf/A-3U_-	3
prop	
124	S
\g__pdfmeta_standard_pdf/A-4_-	str commands:
prop	\str_convert_pdfname:n
124	371
\g__pdfmeta_standard_prop	\str_new:N
..... 13, 16, 20, 24, 34, 42	12
__pdfmeta_standard_verify_-	
handler_annot_action_A:nn . 75, 75	T
__pdfmeta_standard_verify_-	tl commands:
handler_max_pdf_version:nn 60, 61	\c_space_tl
__pdfmeta_standard_verify_-	360
handler_min_pdf_version:nn 52, 53	\tl_if_blank:nTF 294, 302, 310, 318, 326
__pdfmeta_standard_verify_-	\tl_if_eq:nnTF
handler_named_actions:nn .. 68, 69	83
	\tl_if_in:nnTF
	71, 77
	\tl_new:N
	10, 11
	U
	use commands:
	\use:N
	39